PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) (51) International Patent Classification 5: (11) International Publication Number: WO 93/16965 A1 C04B 12/00 (43) International Publication Date: 2 September 1993 (02.09.93) (21) International Application Number: PCT/GB93/00373 (74) Agents: FUNGE, Harry et al.; M'Caw & Co., 41-51 Royal Exchange, Cross Street, Manchester M2 7BD (GB). (22) International Filing Date: 23 February 1993 (23.02.93) (30) Priority data: 27 February 1992 (27.02.92) 92/1457 ZA UA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, (71) Applicants: PRETORIA PORTLAND CEMENT COM-PANY LIMITED [ZA/ZA]; 11 Sherborne Road, Parktown, 2193 Johannesburg (ZA). GOMERSALL, John, Edward [GB/ZA]; 63, Mount Street, Bryanston, 2021 Sandton (ZA). **Published** With international search report. (72) Inventor: FOUCHE, Pierre, Marc; 63, Kammanassie Street, Brackendowns, 1450 Alberton (ZA).

(54) Title: GEOPOLYMERIC BINDER MATERIAL

(57) Abstract

ű,

A dry composition suitable for use as a binder upon being mixed with water, the composition comprising a mixture of an alkaline earth metal compound selected from the group consisting of the oxides and hydroxides of calcium and magnesium, a salt of a cation selected from the group consisting of ammonium, potassium and sodium which is capable of reacting with the alkaline earth metal compound to produce the hydroxide of the cation, a source of silica and a source of an alumina silicate.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
ΑU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinca	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG:	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	ΙE	Ireland	PT	Portugal
BR	Brazîl	IT	Italy	RO	Romania
CA	Canada	JР	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SK	Slovak Republic
CI	Côte d'Ivoire	KZ	Kazakhstan	SN	Senegal
CM	Cameroon	L.J	Liechtenstein	SU	Soviet Union
CS	Czechoslovakia .	LK	Sri Lanka	TD	Chad
CZ	Czech Republic	U.I	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	UA	Ukraine
DK	Denmark	MG	Madagasear	US	United States of America
ES	Spain	MI.	Mali	VN	Viet Nam
Fi	Finland	MN	Mongolia		

-1-

GEOPOLYMERIC BINDER MATERIAL

THIS invention relates to compositions of matter of the type known in the trade as binder and more particularly geopolymeric binders. The term "geopolymeric" is understood in the trade as referring to a material which is composed of or which includes a binder component which has the general chemical formula $(Si-O-Al-O-)_n$, [also known as polysialates], and $(Si-O-Al-O-Si-O-)_n$, [also known as polysialatessilioxos].

5

It is known to produce geopolymers of the type in 10 question by reacting a sodium or potassium silicate solution with an aluminium bearing source material, such as an alumina rich clay, and incorporating a filler material, such as sand and/or stone aggregate into the mixture to produce a castable or mouldable 15 material which may be used in the same manner as cement or concrete. Since the alkali metal silicate contains a large percentage water it is in these applications normally preferred to form the silicate on site by reacting sodium or potassium hydroxide with silica gel 20 [SiO₂]. The product of choice in this regard is sodium hydroxide which is not only very corrosive, but also hygroscopic and expensive. These considerations are at least in part responsible for the low penetration of geopolymers into the conventional porcelanic cement 25 market which cement is based on hydrated calcium silicates.

-2-

5

10

15

20

It is an object of the present invention to provide a dry composition of matter in a form ready to mix with water and filler material and suitable for use as a binder material, e.g. as a conventional cement substitute. It will however be appreciated that the composition may also find various other applications.

According to the present invention there is provided a dry composition suitable for use as a binder upon being mixed with water, the composition comprising a mixture of an alkaline earth metal compound selected from the group consisting of the oxides and hydroxides of calcium and magnesium, a salt of a cation selected from the group consisting of ammonium, potassium and sodium which is capable of reacting with the alkaline earth metal compound to produce the hydroxide of the cation, a source of silica and a source of an alumina silicate.

In one form of the invention the cation salt is selected from the group consisting of the carbonates and hydrocarbonates of ammonium, potassium and sodium, ammonium chloride and ammonium nitrate. In the preferred form of the invention the salt is sodium carbonate. Also in the preferred form of the invention the alkaline earth metal compound is calcium hydroxide.

ċ

The source material of silica and the alumina silicate may be a single composite material. Thus, that source

material may be in the form of an alumino-silicaceous clay. Alternatively, the source may comprise powdered blast furnace slag.

In the preferred form of the invention the source material may at least in part be constituted by flyash. The composition may in addition also include other sources of silica such as, for example, fumed silica condensate.

In the mixture of the composition according to the invention the ingredients may be present in the following stoichiometric equivalent mole ratio:

Alkaline earth metal oxide/hydroxide 1 - 1,2
Cation salt 1
Fly-ash 1
SiO₂ [fumed silica condensate] 1 - 3

Thus, in one specific formulation according to the invention the ingredients may be present in the following mass ratio:

Sodium carbonate 10 - 35 parts

20 Calcium hydroxide 10 - 50 parts

SiO₂ 20 - 80 parts

Fly-ash 50 - 120 parts [depending on the amount of reactive alumina

-4-

silicate present therein!

A preferred composition of this formulation according to the invention comprises the following ingredients in the mass ratio as indicated:

5 Sodium carbonate 24 parts
Calcium hydroxide 38 parts
Fumed silica condensate 60 parts
Fly-ash 100 parts

15

20

The dry composition of the invention may be made into a binder material by mixing it with between 20 and 50 parts of water.

Thus, in the preferred composition comprising 24 parts of sodium carbonate as described above, the dry mix is preferably made up into a wet mix by the addition of 40 parts of water. Sand may be worked into the mix either before or after the addition of water. In accordance with a specific aspect of the invention, however, it is preferred to make up the dry mix with water and thereafter to work the wet mix into up to 300 parts of sand.

According to a second aspect of the invention there is provided a two pack binder mixture comprising a first pack made up of the alkaline earth metal compound, the

-5-

cation salt as defined above and the silica, and a second pack containing the source of alumina silicates.

An example of the invention will now be described without thereby limiting the scope of the invention.

5 EXAMPLE 1

4

A dry mix of powdered ingredients was made up as follows:

		Parts by mass
	Sodium carbonate [NaCO3] -	24
10	Calcium hydroxide [Ca(OH) ₂] -	30
	Silica [Fumed silica condensate] SiO_2 -	60
	Fly-ash -	100

The fly-ash used in the mixture was Class F fly-ash obtained from Matla power station in the Eastern

Transvaal, South Africa and would accordingly have had the following typical composition and ignition properties.

	Constituent	% by Mass		
	\mathtt{SiO}_2	40,04 - 50,6		
20	A12 ^{O3}	26,30 - 38,93		

WO 93/16965

10

15

20

		Fe2 ⁰ 3		2,63	-	5,55
		Ca0		4,42	-	12,80
		MgO		1,15	-	3,10
		50_3		0,16	_	1,13
5		Na_2O		0,30	_	1,03
		K20		0,20	-	0,99
	Loss	upon :	Ignition	0,80	_	3,86

Two test cubes were produced from the above mixture.

In the first instance the four components set out above were thoroughly mixed first on their own and then with 300 parts of sand. 40 Parts of water were then added to the mixture to obtain a wet mix. The wet mix was introduced into a vibrating cubic mould and allowed to set at room temperature. After curing the moulded cube at room temperature for 7 days it was found that the cube had a compressive strength of more than 15 mPa.

In the second instance the Na₂CO₃, Ca(OH)₂ and SiO₂ was first mixed with 40 parts of water whereafter the fly-ash was added and thoroughly mixed. The resulting slurry was then added to the sand [300 parts] and again thoroughly mixed. A cube was produced as described above and was found after 7 days of curing to have a compressive strength of between 18 and 30 mPa.

Countless variations of the invention may be devised

-7-

without departing from the spirit of the invention.

-8-

Claims

5

10

1. A dry composition suitable for use as a binder upon being mixed with water, the composition comprising a mixture of an alkaline earth metal compound selected from the group consisting of the oxides and hydroxides of calcium and magnesium, a salt of a cation selected from the group consisting of ammonium, potassium and sodium which is capable of reacting with the alkaline earth metal compound to produce the hydroxide of the cation, a source of silica and a source of an alumina silicate.

- The composition of claim 1 wherein the cation salt is selected from the group consisting of the carbonates and hydrocarbonates of ammonium,
 potassium and sodium, ammonium chloride and ammonium nitrate.
 - 3. The composition of claim 1 wherein the cation salt is sodium carbonate.
- 4. The composition of claim 1 wherein the alkaline earth metal compound is calcium hydroxide.
 - 5. The composition of claim 1 wherein the source material of silica and the alumina silicate is a single composite material material in the form of an alumino-silicaceous clay or a powdered blast

furnace slag.

WO 93/16965

- 6. The composition of claim 1 wherein the silica and alumina silicate source material is at least in part constituted by fly-ash.
- 5 7. The composition of claim 6 which in addition also includes fumed silica condensate.
 - 8. The composition of claim 1 wherein the ingredien are present in the following stoichiometrate equivalent mole ratio:
- Alkaline earth metal oxide/hydroxide 1 1,2

 Cation salt 1

 Fly-ash 1

 SiO₂ [fumed silica condensate] 1 3
- 9. The composition of claim 8 wherein the ingredients

 are present in the following mass ratio:

Sodium carbonate 10 - 35 parts Calcium hydroxide 10 - 50 parts $5iO_2$ 20 - 80 parts 50 - 120 parts

25 10. The composition of claim 1 in the form of a two pack binder mixture comprising a first pack

-10-

containing of the alkaline earth metal compound, the cation salt as defined above and the silica, and a second pack containing the source of alumina silicates.

International Application No

I. CLASSI	IFICATION OF SUBJ	ECT MATTER (if several classification s	ymbols apply, indicate all)6	
According	g to International Patent	Classification (IPC) or to both National C		
Int.Cl	. 5 CO4B12/O	0		
II. FIELD:	S SEARCHED	1		
		Minimum Docum	entation Searched?	
Classifica	tion System	•	Classification Symbols	
Int.Cl	. 5	CO4B		
		Documentation Searched other to the Extent that such Documents	than Minimum Documentation are Included in the Fields Searched ⁶	
ш. Docu	MENTS CONSIDERE	D TO BE RELEVANT ⁹		
Category o	Citation of Do	cument, 11 with indication, where appropri	ate, of the relevant passages 12	Relevant to Claim No.13
				Account to Claim 140.
Х	FR, A, 2	190 626 (J. DAVIDOVITS	ET AL)	1-5
	26 Marci			
	see page	e 2, line 41 - page 3, e 5, line 16 - line 42;	line 47	
!	1,4,6	= 5, Time 10 - Time 42;	Claims	
Y				6-7
V				,
Υ	6 Novemb	- · 		6-7
	see page	e 1, line 16 - page 2,	line 20	
	see page	3, line 49 - page 4,	line 16	
	See Cla	ms 1-6; examples 1,7;	table 2	
X	EP,A,0 2	262 302 (ANNELIESE ZEME	NTWERKE AG)	1-5
	6 April	1988	•	_ •
	see abst	ract; claims 1-2	A 73 7	,
	See Cold	mn 3, line 11 - column	4, 11ne /	
			-/	
			,	
			•	
•	categories of cited doc	uments: ¹⁰ eral state of the art which is not	"T" later document published after the internal or priority date and not in conflict with th	tional filing date
COI	nsidered to be of particu	lar relevance	cited to understand the principle or theory invention	underlying the
fili	ing date	shed on or after the international	"X" document of particular relevance; the clair	ned invention
which is gived to asythich the publication day of any invo			cannot be considered novel or cannot be convolve an inventive step	
cita	ition or other special re	ason (as specified) oral disclosure, use, exhibition or	"Y" document of particular relevance; the clair cannot be considered to involve an inventi	ve sten when the
otn	ier means		ments, such combined with one or more of ments, such combination being obvious to	ther such doors
"P" doc	cument published prior t er than the priority date	o the international filing date but claimed	in the art. "&" document member of the same patent fami	
IV. CERTI	FICATION		to the factor factor factor factor factor	ily .
	Actual Completion of the	ne International Search	Date of Mailing of the Transport	
	-		Date of Mailing of this International Search	n Keport
	ZŎ M	AY 1993	1 4. 06. 93	
Internationa	Searching Authority		Signature of Authorized Officer	
	EUROPEA	N PATENT OFFICE	OLSSON S.A.	
- DOWNS A				

Form PCT/ISA/210 (second sheet) (January 1985)

9 1

III DOCUME	International Application No							
Category °	MENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)							
Category	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No						
x	GEOPOLYMER 188 vol. 1, pages 93 - 105 J. DAVIDOVITS 'Geopolymeric reactions in	1-5						
K	archaeological cements and in modern blended cements' & CONCRETE INTERNATIONAL vol. 9, December 1987, USA pages 23 - 29 see page 98, line 16 - page 99, line 23 see page 101, line 4 - page 102, line 14	1~5						
	US,A,4 642 137 (R. F. HEITZMANN ET AL) 10 February 1987 see abstract; claims 1,6,11-12 see column 1, line 41 - column 2, line 18 see column 3, line 57 - column 4, line 24; example 1	1-9						
	example 1							

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 9300373 SA 70978

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

28/0 28/05/93

Patent document cited in search report	Publication date	Patent family member(s)		Publication date	
FR-A-2490626	26-03-82				
EP-A-0455582	06-11-91	DE-A- JP-A-	4009998 4228463	02-10-91 18-08-92	
EP-A-0262302	06-04-88	DE-A-	3633736	14-04-88	
US-A-4642137	10-02-87	AU-B- AU-A- JP-B- JP-A-	587638 6355886 4043863 63112444	24-08-89 14-04-88 17-07-92 17-05-88	